



MEDIATOR

Enclosed Emitter Sight User Manual

MD10RD- Red Illumination

MD10GN- Green Illumination



Thanks for choosing Gideon Optics. This short manual will help you understand the features of your new optic, how to mount it, how to change the battery, and how to use it.

WARNINGS:

1. DO NOT observe the sun directly while looking through the optic. The lens coatings are not dark enough to prevent damage to your eyes if you look directly at the sun.
2. Never put this product in a place close to a heat source or a place of high temperature for an extended period of time, like an oven. If you want to change

colors, please use the air-dry variants of Duracoat / Cerakote or simple spray paint.

3. Never leave the optic, mounts, or screws in reach of children or pets, to avoid the potential danger of swallowing.

Specifications

Magnification: 1x

Lens Dimensions: 19mm tall x 16mm wide

Elevation/Windage adjustment range: 45 MOA (Total 90 MOA)

Click Value: 1 MOA per click

Circle Dot Reticle: User Selectable 3 MOA Dot + 38 MOA Circle

Parallax Free: Beyond 33 yards

Red Dot Brightness Setting: 10 levels

Power Supply: 1x CR2032 3V Lithium battery

Auto Wake/Sleep: 225 Seconds after no movement

Shockproof & Waterproof

Dimensions: (LxWxH) 47mm x 35mm x 32mm

Weight (with battery installed): 2.5 oz (approx.)

How to Install/Change the CR2032 Battery

Mediator features a side-mounted battery compartment so the removal of the optic from its mount is not necessary. Remove the battery compartment cap by turning in counter-clockwise direction. Remove the old CR2032 battery and replace with a new 3V CR2032. The "+" side should face outwards, away from the scope body. Replace the battery compartment cap by turning it clockwise. Be careful not to cross-thread to avoid damage to the threads. To avoid stripping out the battery compartment cap, do not over torque it. There is no torque spec on the battery cap, just stop turning when it no longer turns easily.

Power On

Press the "+" shaped UP button (on the left side of the lens) to turn on the sight.

Motion Activation

Mediator features an automatic timeout and motion sensitive "shake to awake" feature. If the optic is not bumped or moved for 225 seconds, the dot will turn off and the optic will enter a low power state, extending battery life. When the optic is bumped or moved, the dot will immediately power on and return to the previously selected brightness level.

Power Off

Mediator can be completely powered off by holding the "-" shaped DOWN button (on the left side of the lens) for three seconds.

NOTE: This is a complete power off that disables the motion-sensitive "wake" function. This is recommended for long term storage, or travel when the optic will not be used.

Brightness Adjustment

Mediator is equipped with 10 brightness settings. Use the UP and DOWN buttons to quickly toggle through the different brightness levels. Always select the lowest brightness setting that still provides good contrast against the target. The higher brightness settings should only be used in bright daylight (otherwise, the reticle will bloom and possibly distort). The sight will return to the previously selected brightness level when powered off and back on.

Reticle Selection

To change between dot, circle-dot, and circle-only reticles, press the “+” shaped UP button and hold it for approximately three seconds. This will cycle between the three available reticles. If the optic is powered off, the optic will return to the previously selected reticle type automatically when powered back on.

Mounting the Sight

If you aren't confident with your abilities, if you don't own an inch pound torque wrench, or if you are unsure about mounting procedure, a local gunsmith won't charge you much to get it right the first time.

Mediator utilizes the same industry standard mounting footprint as Aimpoint® ACRO® and compatible mounting adapters. Mediator is not compatible with other optic footprints. To mount Mediator on the slide of an optics-ready ACRO footprint handgun, loosen the mounting screw on the left side of the optic to remove it from the pre-installed 1913 Picatinny rail mount. Then install Mediator straight onto the ACRO footprint. Front-to-rear play should be minimal. Press the optic forward towards the muzzle and torque the screw down to just ten inch pounds. Applying blue threadlocker to the screw threads can help prevent the screw from loosening up due to the vibrations of firing. For optics-ready handguns, the cover plate (on the slide) may need to be replaced with the appropriate ACRO footprint mounting plate (refer to your handgun operation manual for more details).

Parallax

This sight has been carefully designed to be parallax free at 33 yards. At distances closer than 33 yards, parallax shift should be so minor that it is irrelevant. At distances significantly greater than 33 yards, some parallax may be observed. To reduce the possibility of a point of impact (POI) shift caused by parallax for precision shooting at longer distances, the reticle should be kept in the middle 2/3 of the field of view when aiming.

Reticle, Elevation/Windage Adjustment

This sight uses a 3 MOA dot reticle optionally surrounded by a circle measuring 65 MOA. The elevation and windage dials of this sight feature audible and tactile clicks. Each click will move the point of impact about 1 Minute of Angle (MOA), approximately 1 inch at 100 yards, or 1/2 inch at 50 yards. For zeroing and

precision shooting, always select the lowest brightness setting that still provides good contrast against the target to help the reticle be as crisp and sharp as possible.

Zeroing

Please note that the reticle comes from the factory “centered” in the middle of its adjustment range. Only minor windage and elevation adjustments should be required to zero. If significant adjustments appear necessary, please make sure the sight is properly mounted. This is not a defect of the sight. Adjustable mounting bases (or shims) may be required for certain applications.

After properly mounting the optic to the firearm, fire a 3-shot group and observe the point of impact using an average of the group. Initial zeroing at shorter ranges is recommended before fine-tuning the optic for longer ranges. Zeroing at extremely short distances (10 yards or closer) will likely not provide a true zero at longer ranges due to the angle created by the optic’s centerline height over bore.

Using a small flathead screwdriver, set the elevation dial (top of optic) and the windage dial (side of optic) to adjust the alignment of the reticle. The rotation directions engraved on the optic refer to point of impact shift, not the position of the dot inside the window. Each hash mark on either of the adjustment dials represents one minute-of-angle (MOA). After making your adjustments, fire another 3-shot group to confirm the change in point of impact. Repeat as necessary.

Maintenance:

CLEANING THE LENS

Blow away any dust or grit on the lens surface before wiping the lenses. Gently wipe the lenses clean with a soft and dry cloth. Glass cleaner is fine to use but keep harsh solvents and other gun cleaning chemicals away from the lens.

STORAGE

If possible, Mediator should be stored in a cool and dry place. Remove the battery from the battery compartment if the optic is to be stored for an extended period of time.

NOT USER SERVICABLE

DO NOT attempt to disassemble any components of the Mediator optic. There’s nothing in there you can fix. Disassembling the optic will void the warranty.